Dead Lake Township Right-of-Way Alteration Permit

		- Offine
Owner:		
Mailing Address:		
Phone #:	Email:	
Phone #: Email: Contractor: Contractor Phone #:		
Address where work will be performed:		
Section #:	Parcel #	
Right-of-Way Alteration Requested		
Approach Type: ☐ New	☐ Improved ☐ Temporary	□ Other
Approach Use: ☐ Resid	ential Commercial Fig	eld Access
☐ Sewer ☐ Electrical	☐ Phone Line ☐ Fiber Op	otic
□ Other		- 1.00 - 2.00
Township Road being acces	sed:	
Approach width (20 foot mi	nimum):	
Culvert required: □ No	□ Yes	
Remarks:		
I, the owner/applicant of the above township right-of-way according to follow the requirements set forth, cancel this permit, and charge all	re-mentioned property project, agree to the requirements set by the Board of the Township Board of Supervisors most to the owner/applicant.	to perform all alterations to the of Supervisors. I agree that if I don't hay repair the work as needed or
Owner/Applic	ant	Date
Dead Lake Township Autho	orized Signature	Date
attest that the above mentioned set forth by the Board of Supervis	right-of-way alteration has been perfo ors.	rmed and meets all requirements
Dead Lake Township Autho	rized Signature	Date

Dead Lake Township Road Policies & Standards Article 8 Approach and Driveway Policy

Section 8.1 Design and Construction:

- All new approaches and driveways to Township roads must be approved by the Town Board prior to construction to assure adequate line-of-sight and for determination of necessary drainage.
- 2. Upon the board approval, the Clerk will send the resident the approach policy along with a letter & deposit form. A refundable deposit of \$500.00 must be sent to the Clerk. Upon completion and Township Board approval, the deposit will be refunded after the following meeting. For each occurrence that the Supervisors deem that the installation is not correct, \$100.00 will be deducted from the \$500.00 deposit.
- 3. The cost of constructing or rebuilding an approach or driveway shall be the owner's responsibility.
- 4. No foreign material such as dirt, gravel or bituminous material shall be left or deposited on the road during the construction of an access, driveway or installation of drainage facilities.
- 5. Roadside must be cleaned up after work is completed.
- Approaches and driveways fill slopes shall be constructed 4:1 (4' horizontal to 1' vertical) where existing roadside slopes are 4:1 or better and shall be hand finished and seeded.
- 7. Approaches and driveways shall be so constructed so that they have a minimum hard surface top of no less than 20' and shall slope down and away from the shoulder line of the highway for a distance of at least 15' with a fall of at least 6".
- 8. All new or improved agricultural approaches shall have a minimum of 26' top.
- Culverts, where deemed necessary by the Township Board, are to be provided by the property owner.
- 10. Only new concrete, corrugated meal or corrugated plastic shall be used.
- All culverts shall have a minimum diameter of 15" unless determined otherwise by the Supervisor doing the initial inspection.
- 12. Each line of culvert installed shall be made of only one type and design of material.
- 13. All hard-surfaced driveways that abut a gravel Township road must stop the hard surface material at the road right-of-way and have gravel meet the gravel road.